




Termination Box HTTP-X24

Application


Widely used in FTTH access network.
 Telecommunication Networks
 CATV Networks
 Data communications Networks
 Local Area Networks

Features

- 1) Accommodate 1x4,1x8,1X16 PLC Splitter / PLC Splitter Module;
- 2) Anti-UV(Ultra Violet)
- 3) Up to 24 FTTH Drops;
- 4) 3 inlet ports, 24 outlet ports.
- 5) Grounding device included.
- 6) Ability to store uncut cables.
- 7) Economic design with plastic adaptor panel.
- 8) Accommodate SC SX adaptor
- 9) Applicable for wall/pole-mounted,indoor or outdoor
- 10) Max capacity(F):24 Splices.
- 11) ROHS compliance



HTTP-X24A



HTTP-X24B

Specification

Model	Cable Port	Capacity/PLC splitter	Dimension(mm)	Protection Class
HTTP-X24A	3 cable ports (2 ports for cable with max dia. 15mm, 1 port for cable with max dia. 12mm)	24 Splices,24 SC adaptors 1x4, 1x8, 1x16 PLC splitter	335x275x95	IP 65
HTTP-X24B	+24 drop cable ports	24 Splices, 2 pcs of 1x8 or 1 pc of 1x16 Blade type(LGX type) splitter	335x275x95	IP 65